

CLAIM AMENDMENTS

1 - 9. (canceled)

1 10. (previously presented) An apparatus for applying a
2 coating liquid to a web moving in a travel direction, the apparatus
3 comprising:

4 a hopper defining a distribution chamber extending
5 transversely of the direction, a flow face extending generally in
6 and transverse to the web-travel direction, a slot extending
7 between the chamber and the flow face and elongated transversely of
8 the direction;

9 means for supplying the coating liquid to the chamber,
10 thence through the slot to the flow face, and thence along the flow
11 face and for dropping the liquid as a transversely extending and
12 downwardly flowing curtain from an edge of the flow face onto the
13 web;

14 a pair of transversely spaced edge guides having upper
15 guide elements having transversely confronting faces and fittable
16 complementarily to the flow face, the upper guide elements lying in
17 a use position substantially directly on the flow face to limit
18 liquid flow to a region thereon defined between the transversely
19 confronting faces that hence define the width of the curtain;

20 means for transversely positioning the edge guides and
21 thereby adjusting the curtain width; and

22 respective lower guide elements each having an inner face
23 aligned vertically with the face of the respective upper guide
24 element, the lower guide elements being fixed to and transversely
25 displaceable with the respective upper guide elements.

1 11. (previously presented) The coating apparatus
2 defined in claim 10, further comprising
3 means at lower ends of the lower guide elements for
4 aspirating the coating liquid.

1 12. (previously presented) The coating apparatus
2 defined in claim 10, further comprising
3 means for releasably securing the lower guide elements to
4 the respective upper guide elements.

1 13. (previously presented) The coating apparatus defined
2 in claim 12 wherein the releasable securing means includes finger-
3 operable screws.

1 14. (currently amended) The coating apparatus defined
2 in claim [[9]] 10 wherein the flow-face edge is curved and fits
3 with the upper guide element.

1 15. (currently amended) The coating apparatus defined
2 in claim [[9]] 10 wherein the flow face inclines downward from the
3 slot to the edge.

16. (canceled)

1 17. (currently amended) The coating apparatus defined
2 in claim [[9]] 10, further comprising:
3 a pair of transversely spaced inserts each substantially
4 blocking the slot and the chamber; and
5 means for transversely displacing the inserts and thereby
6 setting a transverse width of the chamber and slot.

1 18. (previously presented) An apparatus for applying a
2 coating liquid to a web moving in a travel direction, the apparatus
3 comprising:

4 a hopper defining a distribution chamber extending
5 transversely of the direction, a flow face extending generally in
6 and transverse to the web-travel direction, a slot extending
7 between the chamber and the flow face and elongated transversely of
8 the direction, and a supply passage opening generally centrally
9 into the chamber;

10 means connected to the passage for supplying the coating
11 liquid centrally to the chamber, thence through the slot to the
12 flow face, and thence along the flow face and for dropping the

13 liquid as a transversely extending and downwardly flowing curtain
14 from an edge of the flow face onto the web;

15 a pair of transversely spaced edge guides having upper
16 guide elements having transversely confronting faces and fittable
17 complementarily to the flow face, the upper guide elements lying in
18 a use position substantially directly on the flow face to limit
19 liquid flow to a region thereon defined between the transversely
20 confronting faces that hence define the width of the curtain;

21 means for transversely positioning the edge guides and
22 thereby adjusting the curtain width;

23 a pair of transversely spaced inserts each substantially
24 blocking the slot and the chamber;

25 means for transversely displacing the inserts and thereby
26 setting a transverse width of the chamber and slot; and

27 structure linking the inserts to the respective guides
28 for joint transverse displacement therewith, the inserts having
29 confronting inner faces aligned vertically with the faces of the
30 respective upper guide elements.

1 19. (previously presented) The coating apparatus defined
2 in claim 18 wherein the hopper includes end plates laterally
3 flanking the inserts and the chambers, the structure including rods
4 passing transversely through the end plates and having inner ends
5 fixed to the inserts.

1 20. (currently amended) The coating apparatus defined
2 in claim [[9]] 18, further comprising
3 means for lifting the upper guide elements off the flow
4 face during transverse displacement of the upper guide elements.